



## SAFETY DATA SHEET (Aerosol) Dash Dandy

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** (Aerosol) Dash Dandy

**Product number** A107-9

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Car maintenance product. - Dressing

**Uses advised against** For professional use only. This product is not recommended for any industrial, professional or consumer use other than the Identified uses above.

#### 1.3. Details of the supplier of the safety data sheet

**Supplier** Autosmart International Ltd  
Lynn Lane,  
Shenstone, nr Lichfield  
Staffordshire. WS14 0DH  
England  
www.autosmartinternational.com  
Tel: +44 (0) 1543 481616 (09:00 - 17:00)  
Fax: +44 (0) 1543 481549 (09:00 - 17:00)  
info@autosmartinternational.com

**Contact person** Mr. Russell Butler

#### 1.4. Emergency telephone number

**Emergency telephone** Mob: +44 (0) 7808 971321 (24hrs)  
Tel: +44 (0) 1543 481616 (09:00 - 17:00)  
Fax: +44 (0) 1543 481549 (09:00 - 17:00)

If you urgently need medical help or advice but it's not a life-threatening situation, call 111 free from any phone to speak to an NHS adviser. The 24-hour NHS 111 service can give you healthcare advice or direct you to the local service that can help you best.

The NHS 111 service will also be available via the harmonised European number for medical advice 116 117

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification

**Physical hazards** Aerosol 1 - H222, H229

**Health hazards** Skin Irrit. 2 - H315 STOT SE 3 - H336

**Environmental hazards** Aquatic Chronic 2 - H411

## (Aerosol) Dash Dandy

**Classification (67/548/EEC or 1999/45/EC)** F+;R12. R52/53.

### Physicochemical

Aerosol containers can explode when heated, due to excessive pressure build-up. The product is extremely flammable and may ignite in the air at normal temperature and pressure. Explosive vapour/air mixtures may be spontaneously formed. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

### 2.2. Label elements

#### Pictogram



#### Signal word

Danger

#### Hazard statements

H222 Extremely flammable aerosol.  
 H229 Pressurised container: may burst if heated  
 H315 Causes skin irritation.  
 H336 May cause drowsiness or dizziness.  
 H411 Toxic to aquatic life with long lasting effects.

#### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P261 Avoid breathing vapour/spray.  
 P264 Wash contaminated skin thoroughly after handling.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

#### Contains

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

#### Supplementary precautionary statements

P271 Use only outdoors or in a well-ventilated area.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves.  
 P302+P352 IF ON SKIN: Wash with plenty of water.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P312 Call a POISON CENTER/doctor if you feel unwell.  
 P332+P313 If skin irritation occurs: Get medical advice/attention.  
 P362+P364 Take off contaminated clothing and wash it before reuse.  
 P391 Collect spillage.  
 P403 Store in a well-ventilated place.  
 P501 Dispose of contents/container in accordance with national regulations.

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

**(Aerosol) Dash Dandy**

<b>PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS</b>		<b>60-100%</b>
CAS number: 68476-85-7	EC number: 270-704-2	REACH registration number: Exempt - Article 2(7)(b)
Substance with a Community workplace exposure limit.		
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Flam. Gas 1 - H220	F+;R12.	
Press. Gas, Liquefied - H280		
<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b>		<b>20-30%</b>
CAS number: 64742-49-0	EC number: 265-151-9	REACH registration number: 01-2119475514-35-xxxx
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Flam. Liq. 2 - H225	Xn;R65. Xi;R38. F;R11. N;R51/53. R67.	
Skin Irrit. 2 - H315		
STOT SE 3 - H336		
Asp. Tox. 1 - H304		
Aquatic Chronic 2 - H411		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

<b>General information</b>	Keep affected person away from heat, sparks and flames.
<b>Inhalation</b>	Move affected person to fresh air at once. Get medical attention if any discomfort continues. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.
<b>Ingestion</b>	Remove affected person from source of contamination. Rinse mouth thoroughly with water. DO NOT induce vomiting. Get medical attention immediately.
<b>Skin contact</b>	Remove affected person from source of contamination. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

##### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	In case of overexposure, organic solvents may depress the central nervous system causing dizziness and intoxication, and at very high concentrations unconsciousness and death.
<b>Ingestion</b>	May cause discomfort if swallowed. Dizziness. Nausea, vomiting. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.
<b>Skin contact</b>	Prolonged contact may cause redness, irritation and dry skin.
<b>Eye contact</b>	May cause temporary eye irritation. Prolonged contact may cause redness and/or tearing.

## (Aerosol) Dash Dandy

### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor** No specific recommendations. If in doubt, get medical attention promptly.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

**Suitable extinguishing media** Extinguish with the following media: Powder. Alcohol-resistant foam. Carbon dioxide or dry powder. Dry chemicals, sand, dolomite etc. Cool aerosol containers exposed to heat with water spray and remove container, if no risk is involved.

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Containers can burst violently or explode when heated, due to excessive pressure build-up. Fire creates: Carbon dioxide (CO<sub>2</sub>). Carbon monoxide (CO). Nitrous gases (NO<sub>x</sub>). Containers can burst violently or explode when heated, due to excessive pressure build-up. The product is highly flammable.

**Hazardous combustion products** Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

#### 5.3. Advice for firefighters

**Protective actions during firefighting** Ventilate closed spaces before entering them. Move containers from fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapours. Do not scatter spilled material with more water than needed to fight the fire. Risk of re-ignition after fire has been extinguished. Control run-off water by containing and keeping it out of sewers and watercourses. Containers close to fire should be removed or cooled with water. Be aware of danger of explosion. Fight advanced or massive fires from safe distance or protected location.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** For personal protection, see Section 8.

#### 6.2. Environmental precautions

**Environmental precautions** Do not discharge into drains or watercourses or onto the ground. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

#### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible.

#### 6.4. Reference to other sections

**Reference to other sections** See Section 11 for additional information on health hazards. For personal protection, see Section 8. For waste disposal, see Section 13.

### SECTION 7: Handling and storage

## (Aerosol) Dash Dandy

### 7.1. Precautions for safe handling

**Usage precautions** Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Read and follow manufacturer's recommendations. During application and drying, solvent vapours will be emitted. Vapours may accumulate on the floor and in low-lying areas. Eliminate all sources of ignition. Static electricity and formation of sparks must be prevented.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Keep away from heat, sparks and open flame. Pressurised container: Must not be exposed to temperatures above 50°C. Store in closed original container at temperatures between 5°C and 30°C. Keep container dry.

**Storage class** Flammable compressed gas storage.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

#### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m<sup>3</sup>

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Long-term exposure limit (8-hour TWA): WEL 1000 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit

### 8.2. Exposure controls

#### Protective equipment



#### Appropriate engineering controls

Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients. No specific ventilation requirements. This product must not be handled in a confined space without adequate ventilation.

#### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

#### Hand protection

No specific hand protection recommended. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Neoprene. Nitrile rubber. Polyethylene. Polyvinyl chloride (PVC). It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

#### Other skin and body protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

## (Aerosol) Dash Dandy

<b>Hygiene measures</b>	Provide eyewash station. Do not smoke in work area. When using do not eat, drink or smoke. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly if skin becomes contaminated.
<b>Respiratory protection</b>	No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Aerosol. Clear liquid. Liquid.
<b>Colour</b>	Colourless.
<b>Odour</b>	Pleasant, agreeable.
<b>Odour threshold</b>	Not available. Not available.
<b>pH</b>	Not applicable. Not applicable.
<b>Melting point</b>	~ 0°C
<b>Initial boiling point and range</b>	~100°C @ 760 mm Hg
<b>Flash point</b>	< -20°C CC (Closed cup).
<b>Evaporation rate</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	Lower flammable/explosive limit: 1.8 % Upper flammable/explosive limit: 9.5 %
<b>Vapour pressure</b>	590 - 1760 kPa @ °C
<b>Vapour density</b>	1.5 - 2.1
<b>Relative density</b>	1.000 @ (20°C)°C
<b>Solubility(ies)</b>	Soluble in water.
<b>Partition coefficient</b>	: 2.3 - 2.8
<b>Auto-ignition temperature</b>	365°C
<b>Decomposition Temperature</b>	Not available.
<b>Viscosity</b>	Not determined.
<b>Oxidising properties</b>	Not applicable.
<b>Comments</b>	Information declared as "Not available" or "Not applicable" is not considered to be relevant to the implementation of the proper control measures.

#### 9.2. Other information

<b>Volatile organic compound</b>	This product contains a maximum VOC content of 574 g/litre.
----------------------------------	---

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

<b>Reactivity</b>	There are no known reactivity hazards associated with this product.
-------------------	---

#### 10.2. Chemical stability

## (Aerosol) Dash Dandy

**Stability** Stable at normal ambient temperatures and when used as recommended. Avoid the following conditions: Heat, sparks, flames. Shocks and physical damage.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Not applicable. Will not polymerise.

### 10.4. Conditions to avoid

**Conditions to avoid** Avoid exposing aerosol containers to high temperatures or direct sunlight. Avoid heat, flames and other sources of ignition.

### 10.5. Incompatible materials

**Materials to avoid** Strong alkalis. Strong acids. Strong oxidising agents.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Nitrous gases (NO<sub>x</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

**Other health effects** There is no evidence that the product can cause cancer.

#### Skin corrosion/irritation

**Human skin model test** Scientifically unjustified.

**Extreme pH** Scientifically unjustified.

**General information** Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

**Inhalation** Vapours may cause headache, fatigue, dizziness and nausea. Vapour may affect central nervous system. Symptoms following overexposure may include the following: Headache. Nausea, vomiting. Intoxication. May cause discomfort. Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting. Vapour may irritate respiratory system/lungs.

**Ingestion** May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach. May cause discomfort if swallowed. No harmful effects expected from quantities likely to be ingested by accident.

**Skin contact** May cause defatting of the skin but is not an irritant.

**Eye contact** Vapour or spray in the eyes may cause irritation and smarting.

**Acute and chronic health hazards** Because of the product's quantity and composition, the health hazard is regarded as low.

**Route of entry** Inhalation Ingestion. Skin and/or eye contact

**Medical symptoms** No specific symptoms noted, but this chemical may still have adverse health impact, either in general or on certain individuals.

**Medical considerations** Skin disorders and allergies.

## SECTION 12: Ecological Information

**Ecotoxicity** The product contains a substance which is harmful to aquatic organisms.

## (Aerosol) Dash Dandy

### 12.1. Toxicity

<b>Acute toxicity - fish</b>	Not determined.
<b>Acute toxicity - aquatic invertebrates</b>	Not determined.
<b>Acute toxicity - aquatic plants</b>	Not determined.
<b>Acute toxicity - microorganisms</b>	Not determined.
<b>Acute toxicity - terrestrial</b>	Not determined.

### 12.2. Persistence and degradability

<b>Persistence and degradability</b>	The product is biodegradable. Volatile substances are degraded in the atmosphere within a few days.
--------------------------------------	---

### 12.3. Bioaccumulative potential

<b>Bioaccumulative potential</b>	Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.
<b>Partition coefficient</b>	: 2.3 - 2.8

### 12.4. Mobility in soil

<b>Mobility</b>	The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces. The product is insoluble in water.
-----------------	--

### 12.5. Results of PBT and vPvB assessment

<b>Results of PBT and vPvB assessment</b>	This product does not contain any substances classified as PBT or vPvB.
---	---

### 12.6. Other adverse effects

<b>Other adverse effects</b>	Not applicable.
------------------------------	-----------------

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>General information</b>	Do not puncture or incinerate, even when empty. Empty aerosols should be recycled where facilities exist. Full or part full aerosols should be disposed of as hazardous waste in accordance with local authority requirements.
<b>Disposal methods</b>	Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Avoid the spillage or runoff entering drains, sewers or watercourses. Packaging: Reuse or recycle products wherever possible.

## SECTION 14: Transport information

### 14.1. UN number

<b>UN No. (ADR/RID)</b>	1950
<b>UN No. (IMDG)</b>	1950
<b>UN No. (ICAO)</b>	1950

### 14.2. UN proper shipping name

<b>Proper shipping name (ADR/RID)</b>	AEROSOLS, flammable
---------------------------------------	---------------------



**(Aerosol) Dash Dandy**

**Proper shipping name (IMDG)** AEROSOLS, flammable

**Proper shipping name (ICAO)** AEROSOLS, flammable

**Proper shipping name (ADN)** AEROSOLS, flammable

**14.3. Transport hazard class(es)**

**ADR/RID class** 2.1

**ADR/RID label** 2.1

**IMDG class** 2.1

**ICAO class/division** 2.1

**Transport labels****14.4. Packing group**

Not applicable.

**14.5. Environmental hazards**

**Environmentally hazardous substance/marine pollutant**

No.

**14.6. Special precautions for user**

**EmS** F-D, S-U

**Tunnel restriction code** (D)

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

**Transport in bulk according to** Not applicable.

**Annex II of MARPOL 73/78 and the IBC Code**

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU legislation** Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).  
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

**Water hazard classification** WGK 1

**15.2. Chemical safety assessment**

No chemical safety assessment has been carried out.

**SECTION 16: Other information**

**General information** Only trained personnel should use this material. This product has been manufactured under ISO 9001 and ISO 14001 Quality and Environmental Management Systems.

## (Aerosol) Dash Dandy

<b>Revision comments</b>	NOTE: Lines within the margin indicate significant changes from the previous revision.
<b>Issued by</b>	Prepared by Autosmart International Ltd, Lynn Lane, Shenstone, Lichfield, Staffordshire, WS14 0DH, Great Britain. www.autosmartinternational.com rbutler@autosmart.co.uk Tel +44 (0)1543 481616
<b>Revision date</b>	24/09/2015
<b>Revision</b>	6
<b>Supersedes date</b>	09/12/2014
<b>SDS status</b>	Approved.
<b>Risk phrases in full</b>	R11 Highly flammable. R12 Extremely flammable. R38 Irritating to skin. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R67 Vapours may cause drowsiness and dizziness.
<b>Hazard statements in full</b>	H220 Extremely flammable gas. H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H229 Pressurised container: may burst if heated H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.