



SAFETY DATA SHEET

(Aerosol) Fuel Injection System Cleaner

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name (Aerosol) Fuel Injection System Cleaner
Product number A36-6

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Car maintenance product.
Uses advised against For professional use only. This product is not recommended for any industrial, professional or consumer use other than the Identified uses above.

1.3. Details of the supplier of the safety data sheet

Supplier Autosmart International Ltd
 Lynn Lane,
 Shenstone, nr Lichfield
 Staffordshire. WS14 0DH
 England
www.autosmartinternational.com
 Tel: +44 (0) 1543 481616 (09:00 - 17:00)
 Fax: +44 (0) 1543 481549 (09:00 - 17:00)
info@autosmartinternational.com

Contact person Mr. Russell Butler

1.4. Emergency telephone number

Emergency telephone Mob: +44 (0) 7808 971321 (24hrs)
 Tel: +44 (0) 1543 481616 (09:00 - 17:00)
 Fax: +44 (0) 1543 481549 (09:00 - 17:00)

If you urgently need medical help or advice but it's not a life-threatening situation, call 111 free from any phone to speak to an NHS adviser. The 24-hour NHS 111 service can give you healthcare advice or direct you to the local service that can help you best.

The NHS 111 service will also be available via the harmonised European number for medical advice 116 117

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Aerosol 1 - H222, H229
Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H336
Environmental hazards Not Classified

(Aerosol) Fuel Injection System Cleaner


Classification (67/548/EEC or 1999/45/EC) Xn;R20/21. Xi;R36/38. F+;R12.

Physicochemical

Aerosol containers can explode when heated, due to excessive pressure build-up. The product is extremely flammable and may ignite in the air at normal temperature and pressure. Explosive vapour/air mixtures may be spontaneously formed. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

2.2. Label elements

Pictogram



Signal word

Danger

Hazard statements

H222 Extremely flammable aerosol.
 H229 Pressurised container: may burst if heated
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing vapour/spray.
 P280 Wear protective gloves.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Contains

ACETONE

Supplementary precautionary statements

P264 Wash contaminated skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P403 Store in a well-ventilated place.
 P501 Dispose of contents/container in accordance with national regulations.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

(Aerosol) Fuel Injection System Cleaner

ACETONE 30-60%		
CAS number: 67-64-1	EC number: 200-662-2	REACH registration number: 01-2119471330-49-xxxx
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	Classification (67/548/EEC or 1999/45/EC) F;R11 Xi;R36 R66 R67	
PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS 30-60%		
CAS number: 68476-85-7	EC number: 270-704-2	REACH registration number: Exempt - Article 2(7)(b)
Substance with a Community workplace exposure limit.		
Classification Flam. Gas 1 - H220 Press. Gas, Liquefied - H280	Classification (67/548/EEC or 1999/45/EC) F+;R12.	
XYLENE 20-30%		
CAS number: 1330-20-7	EC number: 215-535-7	REACH registration number: 01-2119488216-32-xxxx
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Acute Tox. 4 - H312	Classification (67/548/EEC or 1999/45/EC) R10 Xn;R20/21 Xi;R38	
4-HYDROXY-4-METHYLPENTAN-2-ONE 10-15%		
CAS number: 123-42-2	EC number: 204-626-7	REACH registration number: 01-2119473975-21-xxxx
Substance with National workplace exposure limits.		
Classification Flam. Liq. 3 - H226 Eye Irrit. 2 - H319 STOT SE 3 - H335	Classification (67/548/EEC or 1999/45/EC) Xi;R36	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Keep affected person away from heat, sparks and flames.

Inhalation

Move affected person to fresh air at once. Get medical attention if any discomfort continues. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.

(Aerosol) Fuel Injection System Cleaner

Ingestion	Remove affected person from source of contamination. Rinse mouth thoroughly with water. DO NOT induce vomiting. Get medical attention immediately.
Skin contact	Remove affected person from source of contamination. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	In case of overexposure, organic solvents may depress the central nervous system causing dizziness and intoxication, and at very high concentrations unconsciousness and death.
Ingestion	May cause discomfort if swallowed. Dizziness. Nausea, vomiting. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.
Skin contact	Prolonged contact may cause redness, irritation and dry skin.
Eye contact	May cause temporary eye irritation. Prolonged contact may cause redness and/or tearing.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with the following media: Powder. Alcohol-resistant foam. Carbon dioxide or dry powder. Dry chemicals, sand, dolomite etc. Cool aerosol containers exposed to heat with water spray and remove container, if no risk is involved.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up. Fire creates: Carbon dioxide (CO ₂). Carbon monoxide (CO). Nitrous gases (NO _x). Containers can burst violently or explode when heated, due to excessive pressure build-up. The product is highly flammable.
Hazardous combustion products	Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting	Ventilate closed spaces before entering them. Move containers from fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapours. Do not scatter spilled material with more water than needed to fight the fire. Risk of re-ignition after fire has been extinguished. Control run-off water by containing and keeping it out of sewers and watercourses. Containers close to fire should be removed or cooled with water. Be aware of danger of explosion. Fight advanced or massive fires from safe distance or protected location.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

(Aerosol) Fuel Injection System Cleaner

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible.

6.4. Reference to other sections

Reference to other sections See Section 11 for additional information on health hazards. For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Read and follow manufacturer's recommendations. During application and drying, solvent vapours will be emitted. Vapours may accumulate on the floor and in low-lying areas. Eliminate all sources of ignition. Static electricity and formation of sparks must be prevented.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Keep away from heat, sparks and open flame. Pressurised container: Must not be exposed to temperatures above 50°C. Store in closed original container at temperatures between 5°C and 30°C. Keep container dry.

Storage class Flammable compressed gas storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³
Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³
Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

XYLENE

Sk
Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³
Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³

(Aerosol) Fuel Injection System Cleaner

4-HYDROXY-4-METHYLPENTAN-2-ONE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 241 mg/m³

Short-term exposure limit (15-minute): WEL 75 ppm 362 mg/m³

Sk = Can be absorbed through the skin.

WEL = Workplace Exposure Limit

XYLENE (CAS: 1330-20-7)

DNEL	Industry - Inhalation; Short term : 442 mg/m ³ Industry - Inhalation; Long term : 221 mg/kg/day Industry - Dermal; Long term : 3182 mg/m ³ Consumer - Inhalation; Short term : 260 mg/m ³ Consumer - Inhalation; Long term : 65.3 mg/m ³ Consumer - Dermal; : 1872 mg/kg/day Consumer - Oral; Long term : 12.5 mg/kg/day
PNEC	- Fresh water; 0.327 mg/l - Marine water; 0.327 mg/l - Sediment (Freshwater); 12.46 mg/kg - Sediment (Marinewater); 12.46 mg/kg - Soil; 2.31 mg/kg - STP; 6.58 mg/l

4-HYDROXY-4-METHYLPENTAN-2-ONE (CAS: 123-42-2)

DNEL	Industry - Inhalation; Short term : 240 mg/m ³ Industry - Inhalation; Long term : 66.4 mg/m ³ Industry - Dermal; Long term : 9.4 mg/kg/day Consumer - Inhalation; Short term : 120 mg/m ³ Consumer - Inhalation; Long term : 11.8 mg/m ³ Consumer - Oral; Long term : 3.4 mg/kg/day Consumer - Dermal; Long term : 3.4 mg/kg/day
-------------	--

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients. No specific ventilation requirements. This product must not be handled in a confined space without adequate ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

Hand protection

Wear protective gloves. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Neoprene. Nitrile rubber. Polyethylene. Polyvinyl chloride (PVC). It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

(Aerosol) Fuel Injection System Cleaner

Hygiene measures	Provide eyewash station. Do not smoke in work area. When using do not eat, drink or smoke. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly if skin becomes contaminated.
Respiratory protection	No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge. If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator fitted with the following cartridge: Combination filter, type A2/P3.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol. Clear liquid.
Colour	Light (or pale). Red.
Odour	Organic solvents.
Odour threshold	Not available. Not available.
pH	Not applicable. Not applicable.
Melting point	~ 0°C
Initial boiling point and range	~100°C @ 760 mm Hg
Flash point	< -20°C CC (Closed cup).
Evaporation rate	Not available.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 1.8 % Upper flammable/explosive limit: 9.5 %
Vapour pressure	590 - 1760 kPa @ °C
Vapour density	1.5 - 2.1
Relative density	1.000 @ (20°C)°C
Solubility(ies)	Insoluble in water.
Partition coefficient	: 2.3 - 2.8
Auto-ignition temperature	365°C
Decomposition Temperature	Not available.
Viscosity	Not determined.
Oxidising properties	Not applicable.
Comments	Information declared as "Not available" or "Not applicable" is not considered to be relevant to the implementation of the proper control measures.

9.2. Other information

Volatile organic compound	This product contains a maximum VOC content of 716 g/litre.
----------------------------------	---

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---

10.2. Chemical stability

(Aerosol) Fuel Injection System Cleaner

Stability Stable at normal ambient temperatures and when used as recommended. Avoid the following conditions: Heat, sparks, flames. Shocks and physical damage.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not applicable. Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid Avoid exposing aerosol containers to high temperatures or direct sunlight. Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong alkalis. Strong acids. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂). Nitrous gases (NO_x).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Other health effects There is no evidence that the product can cause cancer.

Acute toxicity - dermal

ATE dermal (mg/kg) 7,142.85714286

Acute toxicity - inhalation

ATE inhalation (dusts/mists mg/l) 5.35714286

Skin corrosion/irritation

Human skin model test Scientifically unjustified.

Extreme pH Scientifically unjustified.

General information Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation Harmful by inhalation. Vapours may cause headache, fatigue, dizziness and nausea. Vapour may affect central nervous system. Symptoms following overexposure may include the following: Headache. Nausea, vomiting. Intoxication. May cause discomfort. Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting. Vapour may irritate respiratory system/lungs.

Ingestion May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach. May cause discomfort if swallowed. No harmful effects expected from quantities likely to be ingested by accident.

Skin contact Harmful in contact with skin. May cause defatting of the skin but is not an irritant.

Eye contact Vapour or spray in the eyes may cause irritation and smarting.

Acute and chronic health hazards Because of the product's quantity and composition, the health hazard is regarded as low.

Route of entry Inhalation Ingestion. Skin and/or eye contact

(Aerosol) Fuel Injection System Cleaner

Medical symptoms No specific symptoms noted, but this chemical may still have adverse health impact, either in general or on certain individuals.

Medical considerations Skin disorders and allergies.

Toxicological information on ingredients.**XYLENE**

Other health effects There is no evidence that the product can cause cancer.

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 4,300.0

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,000.0

Species Rabbit

ATE dermal (mg/kg) 1,100.0

Acute toxicity - inhalation

ATE inhalation (dusts/mists mg/l) 1.5

Germ cell mutagenicity

Genotoxicity - in vitro Not available.

Genotoxicity - in vivo Not available.

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

Reproductive toxicity

Reproductive toxicity - development Not available.

Specific target organ toxicity - repeated exposure

Target organs Respiratory system, lungs

Aspiration hazard

Aspiration hazard Kinematic viscosity ≤ 20.5 mm²/s.

Target organs Kidneys Liver Central nervous system

SECTION 12: Ecological Information

Ecotoxicity The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

Ecological information on ingredients.

(Aerosol) Fuel Injection System Cleaner**ACETONE**

Ecotoxicity The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

XYLENE

Ecotoxicity The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

4-HYDROXY-4-METHYLPENTAN-2-ONE

Ecotoxicity The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

12.1. Toxicity

Acute toxicity - fish Not determined.

Acute toxicity - aquatic invertebrates Not determined.

Acute toxicity - aquatic plants Not determined.

Acute toxicity - microorganisms Not determined.

Acute toxicity - terrestrial Not determined.

Ecological information on ingredients.**XYLENE**

Acute toxicity - fish LC50, 96 hours, 96 hours: 4.2 mg/l, Onchorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates EC50, 48 hours, 48 hours: > 2.93 mg/l, Daphnia magna

Chronic toxicity - fish early life stage NOEC, : 3.3 mg/l, Menidia peninsulae (Tidewater silverside)

Chronic toxicity - aquatic invertebrates NOEC, : 6.8 mg/l, Daphnia magna

4-HYDROXY-4-METHYLPENTAN-2-ONE

Acute toxicity - fish LC50, 96 hours, 96 hours: > 100 mg/l,

Acute toxicity - aquatic invertebrates EC50, 48 hours, 48 hours: > 1000 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability The product is biodegradable. Volatile substances are degraded in the atmosphere within a few days.

Ecological information on ingredients.**ACETONE**

(Aerosol) Fuel Injection System Cleaner

Persistence and degradability Volatile substances are degraded in the atmosphere within a few days.

XYLENE

Persistence and degradability Volatile substances are degraded in the atmosphere within a few days.

4-HYDROXY-4-METHYLPENTAN-2-ONE

Persistence and degradability The product is readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.

Partition coefficient : 2.3 - 2.8

Ecological information on ingredients.**ACETONE**

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

XYLENE

Bioaccumulative potential The product contains potentially bioaccumulating substances.

Partition coefficient log Pow: ~ 3.12

4-HYDROXY-4-METHYLPENTAN-2-ONE

Bioaccumulative potential The product is not bioaccumulating.

Partition coefficient log Kow: -0.09

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces. The product is insoluble in water.

Ecological information on ingredients.**ACETONE**

Mobility The product contains volatile organic compounds (VOCs) which have a photochemical ozone creation potential.

XYLENE

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

4-HYDROXY-4-METHYLPENTAN-2-ONE

Mobility The product is soluble in water.

12.5. Results of PBT and vPvB assessment

(Aerosol) Fuel Injection System Cleaner

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

ACETONE

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

XYLENE

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

4-HYDROXY-4-METHYLPENTAN-2-ONE

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects Not applicable.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Do not puncture or incinerate, even when empty. Empty aerosols should be recycled where facilities exist. Full or part full aerosols should be disposed of as hazardous waste in accordance with local authority requirements.

Disposal methods Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Avoid the spillage or runoff entering drains, sewers or watercourses. Packaging: Reuse or recycle products wherever possible.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS, flammable

Proper shipping name (IMDG) AEROSOLS, flammable

Proper shipping name (ICAO) AEROSOLS, flammable

Proper shipping name (ADN) AEROSOLS, flammable

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID label 2.1

(Aerosol) Fuel Injection System Cleaner

IMDG class 2.1

ICAO class/division 2.1

Transport labels**14.4. Packing group**

Not applicable.

14.5. Environmental hazards**Environmentally hazardous substance/marine pollutant**

No.

14.6. Special precautions for user

EmS F-D, S-U

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Water hazard classification WGK 1**15.2. Chemical safety assessment**

No chemical safety assessment has been carried out.

SECTION 16: Other information**General information** Only trained personnel should use this material. This product has been manufactured under ISO 9001 and ISO 14001 Quality and Environmental Management Systems.**Revision comments** NOTE: Lines within the margin indicate significant changes from the previous revision.**Issued by** Prepared by Autosmart International Ltd, Lynn Lane, Shenstone, Lichfield, Staffordshire, WS14 0DH, Great Britain.
www.autosmartinternational.com
rbutler@autosmart.co.uk
Tel +44 (0)1543 481616**Revision date** 24/09/2015**Revision** 6

(Aerosol) Fuel Injection System Cleaner

Supersedes date	02/04/2014
SDS number	10463
SDS status	Approved.
Risk phrases in full	R10 Flammable. R11 Highly flammable. R12 Extremely flammable. R20/21 Harmful by inhalation and in contact with skin. R36 Irritating to eyes. R36/38 Irritating to eyes and skin. R38 Irritating to skin. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness.
Hazard statements in full	H220 Extremely flammable gas. H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H229 Pressurised container: may burst if heated H280 Contains gas under pressure; may explode if heated. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.