



SAFETY DATA SHEET

Matrix Black

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Matrix Black

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Car maintenance product. - Exterior surface coating.

Uses advised against For professional use only. This product is not recommended for any industrial, professional or consumer use other than the Identified uses above.

1.3. Details of the supplier of the safety data sheet

Supplier Autosmart International Ltd
Lynn Lane
Shenstone, nr Lichfield
Staffordshire. WS14 0DH
England
www.autosmartinternational.com
Tel: +44 (0) 1543 481616 (09:00 - 17:00)
SHREQ@autosmart.co.uk

Contact person Mr. Russell Butler

Manufacturer Autosmart International Ltd
Lynn Lane,
Shenstone, nr Lichfield
Staffordshire. WS14 0DH
England
www.autosmartinternational.com
Tel: +44 (0) 1543 481616 (09:00 - 17:00)
info@autosmartinternational.com

1.4. Emergency telephone number

Emergency telephone NCEC - For Chemical Emergency Support ONLY (spill, leak, fire, exposure or accident), Call NCEC at +44 1865 407333 (24Hrs UK)
when calling please quote "AUTOSMART 29003-NCEC"

If you urgently need medical help or advice but it's not a life-threatening situation, call 111 free from any phone to speak to an NHS adviser. The 24-hour NHS 111 service can give you healthcare advice or direct you to the local service that can help you best.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Flam. Liq. 3 - H226

Health hazards Skin Irrit. 2 - H315 Asp. Tox. 1 - H304

Matrix Black

Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms



Signal word Danger

Hazard statements H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H304 May be fatal if swallowed and enters airways.

Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P403+P235 Store in a well-ventilated place. Keep cool.

Supplemental label information EUH066 Repeated exposure may cause skin dryness or cracking.

Contains Distillates (petroleum), hydro- treated light

Supplementary precautionary statements P233 Keep container tightly closed.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P264 Wash contaminated skin thoroughly after handling.
P332+P313 If skin irritation occurs: Get medical advice/ attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.
P405 Store locked up.
P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Distillates (petroleum), hydro- treated light	60-100%
CAS number: 64742-47-8	EC number: 265-149-8
Substance with a Community workplace exposure limit.	
Classification	
Asp. Tox. 1 - H304	

Matrix Black

Siloxanes	5-19%
CAS number: —	
Classification	
Flam. Liq. 3 - H226	
Acute Tox. 4 - H302	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Not considered to be a significant hazard due to the small quantities used. Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.
Ingestion	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
Skin contact	Rinse with water.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue. If it is suspected that volatile contaminants are still present around the affected person, first aid personnel should wear an appropriate respirator or self-contained breathing apparatus. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation.

4.2. Most important symptoms and effects, both acute and delayed

General information	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Not considered to be a significant hazard due to the small quantities used.
Inhalation	A single exposure may cause the following adverse effects: Dryness of mouth and throat. Coughing, chest tightness, feeling of chest pressure. Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death. Congestion of the lungs may occur, producing severe shortness of breath.
Ingestion	May cause irritation. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

Matrix Black

Skin contact Redness. Irritating to skin.

Eye contact A single exposure may cause the following adverse effects: Redness. Irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard. Contains Hydrocarbons. The product is immiscible with water and will spread on the water surface. Not considered to be a significant hazard due to the small quantities used.

Hazardous combustion products Hydrocarbons. Carbon monoxide (CO). Carbon dioxide (CO₂).

5.3. Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Evacuate area. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated.

6.2. Environmental precautions

Environmental precautions Slightly soluble in water. Aquatic toxicity is unlikely to occur. However, large or frequent spills may have hazardous effects on the environment. Absorb spillage with non-combustible, absorbent material. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

6.3. Methods and material for containment and cleaning up

Matrix Black

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Approach the spillage from upwind. Wipe up with an absorbent cloth and dispose of waste safely. The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. The product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. In use may form flammable/explosive vapour-air mixture. Vapours may accumulate on the floor and in low-lying areas. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.

Advice on general occupational hygiene Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store away from incompatible materials (see Section 10). Store in accordance with local regulations. Eliminate all sources of ignition. Take precautionary measures against static discharges. Earth container and transfer equipment to eliminate sparks from static electricity. Keep away from oxidising materials, heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Distillates (petroleum), hydro- treated light

Long-term exposure limit (8-hour TWA): WEL 1000 mg/m³

Short-term exposure limit (15-minute): WEL

WEL = Workplace Exposure Limit.

Distillates (petroleum), hydro- treated light (CAS: 64742-47-8)

Matrix Black

DNEL

Consumer - Oral; Long term : 19 mg/kg/day

Siloxanes

Ingredient comments

No exposure limits known for ingredient(s).

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilating equipment.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment that provides appropriate eye and face protection should be worn. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. The breakthrough time for any glove material may be different for different glove manufacturers. To protect hands from chemicals, wear gloves that are proven to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended. The choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. When used with mixtures, the protection time of gloves cannot be accurately estimated. Gloves made from the following material may provide suitable chemical protection: Nitrile rubber. Thickness: > 0.2 mm The selected gloves should have a breakthrough time of at least 0.5 hours. Glove thickness is not necessarily a good measure of glove resistance as the permeation rate will depend on the exact glove composition. Repeated exposure to chemicals will degrade the ability of the glove to provide resistance to chemicals. Specific work environments and material handling practices may vary, therefore safety procedures should be developed for each intended application. Use thin cotton gloves inside natural rubber gloves if there is an allergy risk to natural rubber.

Other skin and body protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

Hygiene measures

Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.

Matrix Black

Respiratory protection	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'UKCA'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges suitable for intended use should be used. Full face mask respirators with replaceable filter cartridges suitable for intended use should be used. Half mask and quarter mask respirators with replaceable filter cartridges suitable for intended use should be used.
Environmental exposure controls	Keep container tightly sealed when not in use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Clear liquid.
Colour	Water-white.
Odour	Aromatic.
Initial boiling point and range	168 - 176°C
Flash point	55°C Closed cup.
Evaporation rate	< 1 (butyl acetate = 1)
Vapour pressure	< 0.12 hPa @ 20°C
Relative density	~ 0.783 @ 20°C
Comments	Information declared as "Not available" or "Not applicable" is not considered to be relevant to the implementation of the proper control measures.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	See the other subsections of this section for further details.
-------------------	--

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	The following materials may react strongly with the product: Oxidising agents.
---	--

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition. Containers can burst violently or explode when heated, due to excessive pressure build-up. Static electricity and formation of sparks must be prevented. Do not pressurise, cut, weld, drill, grind or otherwise expose containers to heat or sources of ignition.
----------------------------	--

10.5. Incompatible materials

Materials to avoid	Oxidising materials. Acids - oxidising.
---------------------------	---

10.6. Hazardous decomposition products

Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.
---	--

Matrix Black

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

ATE oral (mg/kg) 2,631.58

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

ATE inhalation (dusts/mists mg/l) 7.89

Skin corrosion/irritation

Animal data Irritating.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity None of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Asp. Tox. 1 - H304 May be fatal if swallowed and enters airways. Pneumonia may be the result if vomited material containing solvents reaches the lungs.

General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Matrix Black

Inhalation	A single exposure may cause the following adverse effects: Dryness of mouth and throat. Coughing, chest tightness, feeling of chest pressure. Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death. Congestion of the lungs may occur, producing severe shortness of breath.
Ingestion	May cause irritation. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
Skin contact	Redness. Irritating to skin.
Eye contact	A single exposure may cause the following adverse effects: Redness. Irritation.
Route of exposure	Ingestion Inhalation Skin and/or eye contact
Target organs	No specific target organs known.

Toxicological information on ingredients.

Distillates (petroleum), hydro- treated light

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,000.0

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,000.0

Species Rabbit

Skin corrosion/irritation

Animal data Erythema/eschar score: No erythema (0). Oedema score: No oedema (0). Not irritating.

Human skin model test Not available.

Serious eye damage/irritation

Serious eye damage/irritation Not irritating.

Respiratory sensitisation

Respiratory sensitisation There is no evidence that the material can lead to respiratory hypersensitivity.

Skin sensitisation

Skin sensitisation Buehler test: - Guinea pig: Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro : Negative. This substance has no evidence of mutagenic properties.

Genotoxicity - in vivo : Negative. This substance has no evidence of mutagenic properties.

Carcinogenicity

Carcinogenicity There is no evidence that the product can cause cancer.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEL 750 mg/kg, Oral, Rat

Matrix Black

Inhalation	No specific health hazards known.
Ingestion	Harmful: may cause lung damage if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
Skin contact	No specific health hazards known.
Eye contact	No specific health hazards known.
Medical symptoms	Skin irritation.

Siloxanes

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 2,001.0

Species Rat

ATE oral (mg/kg) 500.0

Acute toxicity - dermal

Summary Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Summary Based on available data the classification criteria are not met.

ATE inhalation (dusts/mists mg/l) 1.5

Skin corrosion/irritation

Skin corrosion/irritation Corrosive to skin.

Serious eye damage/irritation

Serious eye damage/irritation Corrosivity to eyes is assumed.

Respiratory sensitisation

Respiratory sensitisation Not sensitising.

Skin sensitisation

Skin sensitisation Not sensitising.

Germ cell mutagenicity

Summary Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Summary Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

Matrix Black

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

SECTION 12: Ecological information

Ecotoxicity Not considered to be a significant hazard due to the small quantities used.
Transformation due to hydrolysis not expected to be significant.
Transformation due to photolysis not expected to be significant.
The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Ecological information on ingredients.

Distillates (petroleum), hydro- treated light

Ecotoxicity The product components are not classified as environmentally hazardous.
However, large or frequent spills may have hazardous effects on the environment.

Siloxanes

Ecotoxicity The product does not contain organically bound halogen.

12.1. Toxicity

Toxicity Based on available data the classification criteria are not met.

Ecological information on ingredients.

Distillates (petroleum), hydro- treated light

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: > 2-5 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 1.4 mg/l, Daphnia magna

Acute toxicity - aquatic plants IC₅₀, 72 hours: 1-3 mg/l, Algae

Siloxanes

Acute aquatic toxicity

Acute toxicity - fish Not available.

12.2. Persistence and degradability

Persistence and degradability The product contains inorganic substances which are not biodegradable. Volatile substances are degraded in the atmosphere within a few days.

Ecological information on ingredients.

Siloxanes

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.

Matrix Black

Ecological information on ingredients.

Distillates (petroleum), hydro- treated light

Bioaccumulative potential Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.

Siloxanes

Bioaccumulative potential Highly insoluble in water.

12.4. Mobility in soil

Mobility The product is partly soluble in water and may spread in the aquatic environment. The product contains volatile substances which may spread in the atmosphere. The product contains substances which are bound to particulate matter and are retained in soil.

Ecological information on ingredients.

Distillates (petroleum), hydro- treated light

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces. The product is insoluble in water and will spread on the water surface.

Henry's law constant Not available.

Siloxanes

Mobility No data available.

12.5. Results of PBT and vPvB assessment

Ecological information on ingredients.

Distillates (petroleum), hydro- treated light

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current UK criteria.

Siloxanes

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

Ecological information on ingredients.

Siloxanes

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Matrix Black

General information	The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.
Disposal methods	Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Incineration or landfill should only be considered when recycling is not feasible. Vapour from residual product may create a highly flammable or explosive atmosphere inside the container. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Do not cut or weld used containers unless they have been thoroughly cleaned internally.
Waste class	According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

General For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.

14.1. UN number

UN No. (ADR/RID)	1139
UN No. (IMDG)	1139
UN No. (ICAO)	1139
UN No. (ADN)	1139

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	COATING SOLUTION
Proper shipping name (IMDG)	COATING SOLUTION
Proper shipping name (ICAO)	COATING SOLUTION
Proper shipping name (ADN)	COATING SOLUTION

14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

Matrix Black

Transport labels



14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ICAO packing group	III
ADN packing group	III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS	F-E, S-E
ADR transport category	3
Emergency Action Code	•3Y
Hazard Identification Number (ADR/RID)	30
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Health and Safety at Work etc. Act 1974 (as amended). The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"]. EH40/2005 Workplace exposure limits.
----------------------	---

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

EU - EINECS/ELINCS

All the ingredients are listed or exempt.

SECTION 16: Other information

Matrix Black

Abbreviations and acronyms used in the safety data sheet	<p>ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.</p> <p>ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.</p> <p>RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.</p> <p>IATA: International Air Transport Association.</p> <p>ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.</p> <p>IMDG: International Maritime Dangerous Goods.</p> <p>CAS: Chemical Abstracts Service.</p> <p>ATE: Acute Toxicity Estimate.</p> <p>LC50: Lethal Concentration to 50 % of a test population.</p> <p>LD50: Lethal Dose to 50% of a test population (Median Lethal Dose).</p> <p>EC₅₀: 50% of maximal Effective Concentration.</p> <p>PBT: Persistent, Bioaccumulative and Toxic substance.</p> <p>vPvB: Very Persistent and Very Bioaccumulative.</p>
Classification abbreviations and acronyms	<p>Flam. Liq. = Flammable liquid</p> <p>Asp. Tox. = Aspiration hazard</p> <p>Skin Irrit. = Skin irritation</p>
General information	<p>This product is considered to be a small package and is labelled according to the relevant provisions of the legislation.</p>
Classification procedures according to SI 2019 No. 720	<p>Asp. Tox. 1 - H304: Skin Irrit. 2 - H315: : Calculation method. Flam. Liq. 3 - H226: : Expert judgement.</p>
Training advice	<p>Read and follow manufacturer's recommendations. Only trained personnel should use this material.</p>
Revision comments	<p>NOTE: Lines within the margin indicate significant changes from the previous revision. This is the first issue.</p>
Issued by	<p>Prepared by Autosmart International Ltd, Lynn Lane, Shenstone, Lichfield, Staffordshire, WS14 0DH, Great Britain.</p> <p>www.autosmartinternational.com</p> <p>rbutler@autosmart.co.uk</p> <p>Tel +44 (0)1543 481616</p>
Revision date	16/09/2022
Revision	2
Supersedes date	20/11/2019
SDS number	21801
SDS status	Approved.
Hazard statements in full	<p>H226 Flammable liquid and vapour.</p> <p>H302 Harmful if swallowed.</p> <p>H304 May be fatal if swallowed and enters airways.</p> <p>H315 Causes skin irritation.</p> <p>H332 Harmful if inhaled.</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.